### Safety Data Sheet

Printing date 12/11/2015 Revised On 12/11/2015

## 1 Identification of the substance and manufacturer

Trade name: 232 RED ATHLETIC FIELD MARKER

MO00200232

Product code: PC9a Paints and coatings. **Product category** Manufacturer/Supplier: MISSOURI TURF PAINT

1201 E. 63RD STREET KANSAS CITY MO 64110

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.



#### 2 Hazard(s) identification

#### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated. Press. Gas

H319 Causes serious eye irritation Eye Irrit. 2A

**GHS Hazard pictograms** 

GHS02 GHS04 GHS07

Signal word Danger

**Hazard statements** 

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

**Precautionary statements** Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.
Wash hands thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face\_protection.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Protect from sunlight. Store in a well-ventilated place.

#### 3 Composition/information on ingredients

Chemical characterization: Mixtures Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions

| Circinical Eccoription |                   | The product is a mixture of the substances herea below with hornazarasas additions. |        |
|------------------------|-------------------|---|--------|
| Dangerous components:  |                   |   |        |
| 64742-89-8             | VM&P Naphtha      |   | 18.9%  |
| 1317-65-3              | Calcium Carbonate |   | 15.99% |
| 74-98-6                | propane           |   | 12.6%  |
| 106-97-8               | n-butane          |   | 7.4%   |
| 64742-47-8             | Mineral Spirits   |   | 4.53%  |
| 108-65-6               | PM acetate        |   | 3.06%  |

### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Indication of any immediate medical attention needed:

No further relevant information available.

## 5 Fire-fighting measures

Extinguishing agents: Special hazards:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

Dizziness

Protective equipment for firefighters: A respiratory protective device may be necessary

#### 6 Accidental release measures

Personal precautions, protective

equipment and emergency

procedures: Methods and material for

Use respiratory protective device against the effects of fumes/dust/aerosol.

Absorb liquid components with liquid-binding material. containment and cleaning up:

#### 7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. Storage requirements:

Safety Data Sheet

Printing date 12/11/2015 Revised On 12/11/2015

Trade name: 232 RED

(Contd. of page 1)

#### 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

Long-term value: 1800 mg/m³, 1000 ppm Long-term value: 1800 mg/m³, 1000 ppm PEL (USA) REL (USA) refer to Appendix F inTLVs and BEIs book TLV (USA)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm Short-term value: 2370 mg/m³, 1000 ppm TLV (USA)

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

Hygienic protection: Wash hands after use

Do not eat or drink while working. **Breathing equipment:** 

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

#### 9 Physical and chemical properties

Aerosol.

Appearance: Odor threshold: Not determined. pH-value: Melting point/Melting range Not determined. Undetermined. Boiling point: -44 °C (-47 °F) -19 °C (-2 °F) Flash point: Flammability (solid, gas): Extremely flammable. Not determined.

Decomposition temperature:

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: Upper Explosion Limit: 1.7 Vol % 10.9 Vol %

Vapor pressure: Relative Density: Not determined. Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. Evaporation rate Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. VOC content: 487.2 g/l / 4.07 lb/gl

VOC content (less exempt solvents):

47.4 % 26.2 % Water: MIR Value: 0.58 Solids content: 25.2 %

## 10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Chemical stability: Not fully evaluated.

No dangerous reactions known.

Possibility of hazardous reactions: Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

## 11 Toxicological information

# LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

108-65-6 PM acetate

LD50 8500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

(Contd. on page 3)

## Safety Data Sheet

Printing date 12/11/2015 Revised On 12/11/2015

Trade name: 232 RED

(Contd. of page 2)

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Hazardous for water, do not empty into drains.

Aquatic toxicity: Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

**UN-Number** UN1950 N/A

DOT Consumer Commodity ORM-D

Aerosols, flammable

1950 Aerosols

Transport hazard class(es):

2.1

Marine pollutant: No

Warning: Gases F-D,S-U Special precautions for user:

EMS Number:

On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg **Quantity limitations** 

ADR

Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity

**IMDG** 

Limited quantities (LQ)

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Packaging Group: UN "Model Regulation": UN1950, Aerosols, 2.1

## 15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. CPSC:

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

EPA:

None of the ingredients is listed.

16 Other information

Regulatory Affairs 12/11/2015 / -Contact: Date of preparation / last revision