4383-S 05 00

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION PRODUCT NUMBER HMIS CODES Health Flammability 0 Reactivity 0 4383-S PRODUCT NAME Athletic Field Marking Paint, Grass Green MANUFACTURER'S NAME EMERGENCY TELEPHONE NO. MAUTZ PAINT CO. (216) 566-2917939 E. Washington Ave. Madison, WI 53707 DATE OF PREPARATION INFORMATION TELEPHONE NO. 11-DEC-04 (216) 566-2902 ______ Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS
% by WT CAS No. INGREDIENT UNITS VAPOR PRESSURE 3 14807-96-6 Talc ACGIH TLV 2 mg/m3 as Resp. Dust
OSHA PEL 2 mg/m3 as Resp. Dust
471-34-1 Calcium Carbonate
ACGIH TLV 10 mg/m3 as Dust
OSHA PEL 15 mg/m3 Total Dust
OSHA PEL 5 mg/m3 Respirable Fraction 48 ______ Section 3 -- HAZARDS IDENTIFICATION ROUTES OF EXPOSURE INHALATION of vapor or spray mist. EYE or SKIN contact with the product, vapor or spray mist. EFFECTS OF OVEREXPOSURE EYES: Irritation. SKIN: Prolonged or repeated exposure may cause irritation. INHALATION: Irritation of the upper respiratory system.
In a confined area vapors in high concentration may cause headache, nausea or dizziness. SIGNS AND SYMPTOMS OF OVEREXPOSURE Redness and itching or burning sensation may indicate eye or excessive skin exposure. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE None generally recognized.

For complete discussion of toxicology data refer to Section 11.

Continued on page 2

CANCER INFORMATION

4383-S page 2

Section 4 -- FIRST AID MEASURES

Flush eyes with large amounts of water for 15 minutes.

Get medical attention.

Wash affected area thoroughly with soap and water. SKIN:

Remove contaminated clothing and launder before re-use.

If affected, remove from exposure. Restore breathing. Keep warm and quiet. INHALATION:

INGESTION: Do not induce vomiting.

Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

LEL UEL N.A. N.A. FLASH POINT Not Applicable

FLAMMABILITY CLASSIFICATION

Not Applicable EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY

Not Applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

4383-S page 3 ______

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction)

(total dust), 5 mg/m3 (respirable fraction).

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority. VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive. PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2. EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

13.01 lb/gal 1558 g/l 1.57 212 - 213 F 100 - 100 C PRODUCT WEIGHT SPECIFIC GRAVITY
BOILING POINT
MELTING POINT Not Available MELTING POINT VOLATILE VOLUME 55 % Slower than ether Heavier than air EVAPORATION RATE VAPOR DENSITY VAPOR DENSIII SOLUBILITY IN WATER N.A. 9.5 VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)

0.34 lb/gal 40 g/l Less Water and Federally Exempt Solvents 0.15 lb/gal 18 g/l Emitted VOC

4383-S page 4 ______

Section 10 -- STABILITY AND REACTIVITY

STABILITY -- Stable

CONDITIONS TO AVOID

None known. INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

TOXICOLOGY DATA

CAS No. Ingredient Name

14807-96-6 Talc

LC50 RAT 4HR Not Available LD50 RAT Not Available

471-34-1 Calcium Carbonate

LC50 RAT 4HR Not Available

LD50 RAT Not Available

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product is not hazardous as defined under the Resource

Conservation and Recovery Act (RCRA) 40 CFR 261.

Incinerate in approved facility. Do not incinerate closed container.

Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

No data available.

Section 15 -- REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

4383-S page 5

CAS No. CHEMICAL/COMPOUND % by WT % Element

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.