

MATERIAL SAFETY DATA SHEET

MSDS Name: SCR-17 SATURN YELLOW PAINT

Revision Date: 01/11/10
Page Number: 1 of 6

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: SCR-17 SATURN YELLOW PAINT
CAS Number: MIXTURE
HMIS Rating: Health: 1 Fire: 1 Reactivity: 0

Company Identification: DAY-GLO COLOR CORP.
4515 SAINT CLAIR AVENUE
CLEVELAND OH 44103

Telephone/Fax: (216) 391-7070 (216) 391-7751
Chemtrec (24 hr. Emergency) (800) 424-9300

Product Class: WATER BASED PAINT
Trade Name: SATURN YELLOW PAINT
Product Code: SCR-17

SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent
(No hazardous ingredients known at this time.)		

SECTION III - HAZARDS IDENTIFICATION

EYE CONTACT
May cause irritation.

SKIN CONTACT
May cause irritation.

INHALATION HAZARDS
Outgassing of formaldehyde vapors can be irritating.

INGESTION HAZARDS
Small amounts swallowed are not likely to cause injury. Not a hazard in normal industrial use.

TARGET ORGANS
No organs affected.

CANCER HAZARDS
This product contains less than 0.1% free formaldehyde and may be capable of outgassing formaldehyde at levels in excess of OSHA's Action Level under some conditions of use. Formaldehyde is a

MATERIAL SAFETY DATA SHEET

MSDS Name: SCR-17 SATURN YELLOW PAINT

Revision Date: 01/11/10

Page Number: 2 of 6

potential cancer hazard. Long term exposure may result in dermatitis or respiratory sensitization for sensitive individuals.

SECTION IV - FIRST AID MEASURES

EYE CONTACT

Immediately flush with water for at least 15 minutes while holding eyelids open. Call a physician.

SKIN CONTACT

Practice good industrial hygiene. Wash with soap and water.

INHALATION

Remove to fresh air. Treat symptoms. Call a physician.

INGESTION

Do not induce vomiting. Give water. Call a physician.

SECTION V - FIRE-FIGHTING MEASURES

Flammability Class	NA
Flash Point:	None
Explosive Range:	None
	None

FLAMMABLE PROPERTIES

Water based. Difficult to ignite unless directly involved in flame. Exposure to heat will produce irritating vapors.

EXTINGUISHING MEDIA

Use dry chemical, alcohol foam, carbon dioxide or water spray when fighting fires involving this material.

FIRE FIGHTING INSTRUCTIONS

Keep unnecessary people away. Isolate area. Stay upwind. Wear self-contained breathing apparatus.

SECTION VI - ACCIDENTAL RELEASE MEASURES

CONTAINMENT

Contain with absorbent material such as clay, soil, or any commercially available absorbent. Dike to prevent entry to sewer systems.

CLEAN-UP

Place in an appropriate recovery or salvage drum for disposal.

MATERIAL SAFETY DATA SHEET

MSDS Name: SCR-17 SATURN YELLOW PAINT

Revision Date: 01/11/10

Page Number: 3 of 6

CERCLA/SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (TITLE III)

This is not a regulated material under 40 CFR 117, 302. Notification of spills is not required.

EVACUATION

Not normally necessary. Refer to your organization's Release Response Procedures.

SECTION VII - HANDLING AND STORAGE

HANDLING

Use in a well ventilated area.

STORAGE

Keep away from heat, sparks, and flame. Store in a cool place.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
-----------	-------------	------------	-----------	----------

No exposure limits have been established for this product.

ENGINEERING CONTROLS

General ventilation is recommended. Additional local exhaust ventilation is recommended where dusts, mists, or vapors may be released.

RESPIRATORY PROTECTION

A NIOSH approved respirator with a combination formaldehyde/HEPA cartridge is recommended.

PERSONAL PROTECTIVE EQUIPMENT

Where contact is likely, chemical resistant gloves and safety glasses or goggles are recommended.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Appearance/Color:	Yellow
Odor:	Pungent
Solubility (in water):	N/A
Boiling Range:	212-220 F

Evaporation Rate: Slower than n-Butyl Acetate

MATERIAL SAFETY DATA SHEET

MSDS Name: SCR-17 SATURN YELLOW PAINT

Revision Date: 01/11/10
Page Number: 4 of 6

Vapor Density: Heavier than air
% Volatile Weight 38.86%
% Volatile Volume: 43.7%
Weight/Gallon: 9.48
VOC 22 g/l

SECTION X - STABILITY AND REACTIVITY

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

CONDITIONS TO AVOID

Heat, sparks, and open flame.

INCOMPATIBILITIES

Strong acids and bases.

HAZARDOUS DECOMPOSITION PRODUCTS

In the event of combustion, oxides of carbon, nitrogen and sulfur will be formed.

SECTION XI - TOXICOLOGICAL INFORMATION

No toxicological studies have been conducted on this product.

SECTION XII - ECOLOGICAL INFORMATION

No studies have been conducted on this product.

SECTION XIII - DISPOSAL

Dispose of in accordance with local, state, and federal regulations.

SECTION XIV - TRANSPORT INFORMATION

UN Number NOT REGULATED
Packaging Group
Hazard Class
Shipping Name

SECTION XV - REGULATORY INFORMATION

SARA TITLE III SECTION 313:

This product contains no chemicals subject to the reporting requirements of

MATERIAL SAFETY DATA SHEET

MSDS Name: SCR-17 SATURN YELLOW PAINT

Revision Date: 01/11/10

Page Number: 5 of 6

Section 313 of the Emergency Planning and Community Right-to-Know Act.

CALIFORNIA PROPOSITION 65 (CARCINOGEN)

This product contains a chemical known to the state of California to cause cancer.

Ingredient Name	CAS Number
FORMALDEHYDE	00050-00-0

OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200

This product is not considered hazardous as defined.

SARA SECTIONS 311 AND 312

Reporting of this product is not required.

TOXIC SUBSTANCES CONTROL ACT (TSCA)

All components in this product are listed, or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) 8(b) Inventory.

CLEAN WATER ACT

This product contains no ingredients regulated by the Clean Water Act.

CLEAN AIR ACT

This product contains no ingredients regulated by the Clean Air Act.

HAZARDOUS AIR POLLUTANTS (HAPS)

This product contains no Hazardous Air Pollutants (HAP's).

CLEAN AIR ACT AMMENDMENTS (ODS)

No DAY-GLO product contains an ozone depleting substance (ODS), nor are any of our products manufactured with them.

COALITION OF NORTHEAST GOVERNORS (CONEG)

This product is in compliance with CONEG (i.e., total cadmium, chromium, lead and mercury < 100 ppm).

FDA 21 CFR

DAY-GLO Color Corp. products are not listed by the FDA for use under 21 CFR since potential applications are so numerous that specific applications must be submitted to the FDA for inclusion in the 21 CFR FDA listing.

SECTION XVI - OTHER INFORMATION

MATERIAL SAFETY DATA SHEET

MSDS Name: SCR-17 SATURN YELLOW PAINT

Revision Date: 01/11/10

Page Number: 6 of 6

LABEL INFORMATION

SCR-17 SATURN YELLOW PAINT

HEALTH - 1 FLAMMABILITY - 1 REACTIVITY - 0

PRECAUTIONS: Contains less than 0.1% formaldehyde a potential cancer hazard. May outgas to levels above OSHA's action level with possible respiratory sensitization. Do not freeze. Avoid contact with skin and eyes. Use appropriate respirator if product can form mists or vapors.

FIRST AID: EYES: Flush for 15 min. SKIN: Wash with soap & water

INGESTION: Give water, do not induce vomiting. Call a physician.

FIRE FIGHTING USE: Water, dry chemical, CO2, foam (water miscible).

SPELL CONTROL: Dike to prevent spread or entry to sewer. Remove ignition sources. Absorb on inert material & incinerate.

CONTAINS:

CAS NO. OR NJ TSRN:

WATER	07732-18-5
RESIN	39277-28-6
ACRYLIC COPOLYMER	N/A
RESIN	N/A
PROPYLENE GLYCOL	00057-55-6

TARGET ORGANS: NO ORGANS AFFECTED.

MATERIAL V.O.C.: 22 g/l

CALIFORNIA PROP 65: This product contains a component known to the state of California to cause cancer: Formaldehyde (50-00-0).

NOTE - Additional information is available from your Employer & the Material Safety Data Sheet.

DISCLAIMER

The information contained herein is believed to be accurate, but is not warranted. Nothing contained herein constitutes a specification, nor is it intended to warrant suitability for the intended use.
